

Sunlight Readable Open Frame TFT Monitor

JOF17SHB 17.1" SXGA Open Frame Color TFT Display



Environment Specifications

Operating Temperature	0~50 C (32~122 F)
Storage Temperature	-20~60 C (-4~140 F)
Relative Humidity	10~70% @40 C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)

Mechanical Specifications

Construction	Steel chassis
Dimensions	392(W) x 323(H)x 50(D)mm

Display Specifications

Display	17.1" Color Active TFT Flat Panel Display
Luminance	1000 cd/m
Contrast Ratio	300/1
Pixel Pitch	0.264 mm
Viewing Angle	160/160 (H/V)
Resolutions	1280 x 1024 (native mode), 16M colors
LCD MTBF	40,000 hrs
Touch Screen	Analog resistive (optional) or SAW (optional)
Power Consumption	35w Max
OSD Control	On the back side
I/O Connectors	1xDC power input, 1xVGA, optional: DVI, S-Video, RCA
Power Input	DC 12V
Weight	3.0kg
IP Grade (Back)	IP30
IP Grade (Front)	IP40

Mechanical Dimensions

