

Sunlight Readable Open Frame TFT Monitor

JOF15SHB 15.1" SVGA Open Frame Color TFT Display



Environment Specifications

Operating Temperature	0~50 C (32~122 F)
Storage Temperature	-20~60 C (-4~140 F)
Relative Humidity	10~90% @40 C Non-condensing, without touch screen
Vibration	1G peak, 5~500 Hz (Random)
Shock	15G peak acceleration (11 msec. duration)

Mechanical Specifications

Construction	Steel chassis
Dimensions	300(W) x 240(H)x 46(D)mm

Display Specifications

Display	15.1" Color Active TFT Flat Panel Display
Luminance	1000 cd/m
Contrast Ratio	300/1
Pixel Pitch	0.264 mm
Viewing Angle	160/160 (H/V)
Resolutions	1024 x 768 (native mode), 16M colors
LCD MTBF	40,000 hrs
Touch Screen	Analog resistive (optional) or SAW (optional)
Power Consumption	30w Max
OSD Control	On the back side
I/O Connectors	1xDC power input, 1xVGA, optional: DVI, S-Video, RCA
Power Input	DC 12V
Weight	1.3kg
IP Grade (Back)	IP30
IP Grade (Front)	IP40

Mechanical Dimensions

